

WideTEK[®] 36CL

WideTEK 36CL-600

*Ultra fast, attractively priced
scanner for technical documents,
with built in computer and software*

***Fastest and highest quality color CIS
scanner on the market
Made in Germany at lowest prices***



© 10_2016 / EN



- SCANS UP TO 36 INCH
- FEEDS UP TO 38 INCH
- 1200 x 1200 DPI SCANNER RESOLUTION
- FAST SCANS: 10 INCHES PER SECOND AT 200 DPI IN FULL COLOR
- ENDLESS SCANNING - SCAN UNLIMITED LENGTHS TO MULTIPAGE PDF
- INTEGRATED 64BIT LINUX, INTEL QUAD CORE, 8 GB RAM, 128GB SSD
- GIGABIT TCP/IP NETWORK INTERFACE
- SUPPORTS SRGB, ADOBE RGB, NATIVE COLOR SPACES
- LARGE WVGA COLOR TOUCHSCREEN FOR SIMPLIFIED OPERATION
- INTEGRATED WALK UP SCANNING SOFTWARE
- FACE UP SCANNING
- CENTER FEED, LEFT OR RIGHT SIDE FEED
- AUTOMATIC SIZE AND POSITION DETECTION
- AUTOMATIC CROP AND DESKEW
- DURABLE, ANTISTATIC, ALL METAL PAPER PATH
- VIRTUAL RESCAN, MODIFY IMAGES WITHOUT RESCANNING
- OPTIONAL EXTERNAL FULL HD TOUCHSCREEN
- BUILT TO LAST
- EASY INSTALLATION VIA SCAN2NET® TECHNOLOGY



The WideTEK® 36CL-600, a true standalone system with built in computer and software, raises the bar again. This scanner for technical documents is the most complete solution on the market today, available at an extremely attractive price.

Professional quality. Made in Germany.

Fastest color CIS scanner at the lowest possible price. Delivers images in brilliant quality with excellent color accuracy

The WideTEK® 36CL-600 is by far the fastest color CIS scanner on the market, running at 10 inches per second at 200 dpi in full color. At the full width of 36" and 600dpi resolution, the scanner still runs at 1.7 inches per second. Grayscale and binary speeds are doubled, but are limited to 10ips to ensure safe paper handling. All of these speeds are guaranteed, due to the Scan2Net® technology integrated in the scanner's own built in 64 bit Linux PC. It is a true standalone system, capable of scanning directly to FTP servers, hot folders, USB drives, to cloud applications in the internet or copying to printers directly, without the need for an extra PC.

The WideTEK® 36CL produces extraordinarily sharp images, with color accuracy even superior to competing CCD scanners. Document rotation is done on the fly, a scan of an E-sized / A0 document in portrait mode at 300 dpi in 24bit color takes less than 6 seconds to scan and another 2 seconds to crop & deskew, preview and store.



Further highlights that make the WideTEK® 36CL scanner the best choice for many application:

- Scan2USB – Walk up scanning to a USB device
- Scan2Print – Copy to networked printers or hot folders
- Scan2Network – Output to network resources, SMB, FTP
- Output formats: PDF, PDF/A, JPEG, TIFF, PNM, Multipage PDF and TIFF, DICOM
- Virus resistant Linux OS
- OS independent, runs with Windows 7, 8, 10, Linux, Mac
- ScanWizard uses any browser: IE, Safari, Chrome, Firefox
- Remote maintenance and troubleshooting
- Firmware updates via web interface
- Wide color gamut, supports sRGB, Adobe RGB, native RGB

Options:

- MFP solution via Print Wizard for Canon (iPF and OCE), HP (DesignJet and PageWide) and other printers.
- Floor stand with paper catch
- External full HD 22" touchscreen
- Batch Scan Wizard for high volume scanning
- Productivity kit with document return guides and exit tray
- Full Coverage Warranty – Up to 5 years, free spare parts & more



Large documents like maps rewind to the front or fall into the paper catch. A USB 3.0 port let you take away your scanned images on a USB device.

Markets and Applications

WideTEK® 36CL-600, a valuable production device for numerous markets

WideTEK® 36CL-600 Markets

- AEC, Architecture, Engineering, Construction, CAD
- Utility Companies, Developers, Government
- Copy Services, Reprographics
- GIS, Mapping Services
- Media Control, Press Clipping Services
- Universities, Libraries, Registries

The applications are many and diverse. WideTEK® 36CL-600 for nearly any application where you need wide format and production speeds.

WideTEK® 36CL-600 Applications

- Scanning of maps, color posters, display graphics,
- Reproducing artwork, photographs
- Scanning of engineering and architectural CAD drawings
- Production scanning of newspapers, periodicals and magazines
- Digitizing documents from government offices and registries
- Archiving and copying blueprints and sepias

The Scan2Net® platform is the technological foundation of all WideTEK® and Bookeye® scanners from Image Access. It replaces the proprietary scanner drivers and software that traditional scanners require with the fastest common, nonproprietary inter-device connection available: TCP/IP over Ethernet. With network interface speeds much higher than USB 2 or USB 3 scanners, Scan2Net® devices are able to reach unrivaled performance at extremely low connectivity cost.

Scan2Net® scanners feature a 64bit Linux based operating system, dedicated to scanner specific imaging and mechanical control tasks, maximizing scanning speeds and performance.

Scan2Net® Advantages

- 64bit Linux based computer, fast and virus protected
- Easy integration into existing network structures
- Only a single IP address is required to run the scanner
- Integration and remote access via the Intranet or even the Internet
- Scans directly to SMB, FTP, hot folders, USB, Email or the Cloud without the need of an external PCs
- Simple, intuitive operation, Java and HTML based
- Clear menu structure, operation via touchscreen
- Multilanguage support, customizable user interface

TECHNICAL DATA

Maximum Document Size	965 mm (38 inch)
Maximum Scan Width	915 mm (36 inch)
Scanner Resolution / Optical Resolution	1200 x 1200 dpi (optionally 9600 x 9600 dpi interpolated) / 1200 x 600 dpi
Speed 24 bit Color, full 36" width	200 dpi - 15 m/min (10 inch/s), 300 dpi - 12 m/min (8 inch/s) 600 dpi - 2.5 m/min (1.7 inch/s), 1200 dpi - 1.3 m/min (0.85 inch/s)
Color Depth	48 bit color, 16 bit grayscale
Scan Output	24 bit color, 8 bit grayscale, bitonal, enhanced halftone
File Formats	PDF, PDF/A, JPEG, PNM, TIFF uncompressed, TIFF G4 (CCITT), Multipage PDF and TIFF, DICOM
ICC Profiles	Embedded for sRGB, Adobe RGB and native. Individual profiling via web based Scan2ICC subscription
Camera	3x CIS modules, 22,389 pixels, encapsulated and dust-proof
Light source	Dual light illumination, no shadows or wrinkles visible
Computer	64 bit Linux, Intel quad core processor, 8 Gigabyte RAM, 128GB SSD for very long scans
Interface	1 GBit Fast Ethernet with TCP/IP based Scan2Net® Interface
Dimension	195 x 1100 x 410 mm (7.7 x 43.3 x 16.1 inch) (H x W x D)
Weight	28 kg / 62 lbs.
Electrical Connection	100 – 240 V AC, 47 – 63 Hz (external power supply, complies with ECO standard CEC level VI)
Power Consumption	≤ 0.5 W (Sleep) / 2.8 W (Standby) / 45 W (Scanning)
Operating Temperature	5 to 40 °C, 40 to 105 °F
Relative Humidity	20 to 80 % (non-condensing)
Noise	< 35 dB(A) (Scanning) / < 25 dB(A) (Standby)
Approvals	ANSI/UL 60950-1, CAN/CSA C22.2 No. 60950-1; IEC 60950-1; FCC 47 Part 15, EN 55022, EN 55024



WEEE

RoHS



Jebel Ali Free Zone, Dubai (H0)
Street No. N503 - FD03, FD04 & FD05
United Arab Emirates
P.O. Box 17020

Tel: +971 (4) 881 44 40
Fax: +971 (4) 881 42 42
www.forefrontec.com

Al Olaya Street, Riyadh (B0)
Akariyah-3 Building, Office
610 Kingdom of Saudi Arabia
P.O. Box 301807, Riyadh 11372

Tel: +966 (11) 460 35 80
Fax: +966 (11) 460 35 85

IMAGE ACCESS GMBH

Hatzfelder Str. 161-163
42281 Wuppertal, Germany
Tel.: +49 (0)202 27058-0
www.imageaccess.de

IMAGE ACCESS LP

Crystal Lake, IL 60014, USA
Office: +1 (779) 220-4662
Sales: +1 (727) 612-0809
www.imageaccess.us

Technical changes, errors and omissions excepted.
All information subject to change. © Image Access GmbH 2016